




RING



Features:

High Quality Bendable Aluminum with high standard 6063-T6 aluminum stronger than 6063-T5, deep anodizing (more than 12µm) of profile protects the aluminum against corrosion, extends durability.

The Anti yellowing PMMA Diffuser and wide profile with discerning elegance, allowing it to seamlessly fit into any interior.

UV stabilized Diffuser, no inclusions or scratches on the surface.

Ring pendant creates a warm inviting glow by emitting smooth and seamless light.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.

Wattag : 20 - 40W/M

Luminaire Efficacy: 100lm/W

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: Linear Rigid Module

Diffuser: Anti yellowing PMMA

Operating Temperature: -20°C to 50°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at ta 25°C
(L80/B10)

Fields of Application:

Retail

Education

Galleries hotels

Living spaces

Installation Method:

Suspended

Wattage(W)/M :	20	40	Customized		
Finish :	White(W)	Black(B)	Silver(S)	Customized(C)	
Kelvin* :	3000K	4000K	6000K	6500K	Tunable
Beam Angle :	120°				
CRI :	80+	90+			
Driver :	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth
Diameter :	500	1000	1250	1500	2000 Customized

*Special Color and Finish on request


Product Code (964484240):

Wattage/M	Lumens(LM)	Dimension(W x H) mm
20	2000LM	48 x 42
40	4000LM	48 x 42

*Luminous flux value is calculated for 4000K and CRI>80.

*Above mentioned wattages can be customized according to designed requirement.

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 964484240 30K 120D 8 1 W 5

CCT	Beam Angle	CRI	Driver	Finish	Diameter	
30K -	120D - 120°	8-	1 - ON/OFF	W-White	500	
3000K		>80	2 - 0/1-10V	B-Black	1000	
40K -		9-	3 - DALI	S-Silver	1250	
4000K		>90	4 - Phase	C-	1500	
60K -			Dimming	Customized	2000	
6000K				5 - Bluetooth	Customized	
65K -						
6500K						
TuK -						
Tunable						

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C