


RING




Features:

High Quality Bendable Aluminum with high standard 6063-T6 aluminum stronger than 6063-T5, deep anodizing (more than 12µm) of profile protects the aluminum against corrosion, extends durability.

The Anti yellowing PMMA Diffuser and wide profile give the discerning elegance, allowing it to seamlessly fit into any interior.

Diffuser is UV stabilized, no inclusions or scratches on the surface.

Ring pendant creates a warm inviting glow by emitting light from both above and below the rings.



Technical Specifications:

Input Voltage : 220- 240 V AC, 50 Hz.

Wattage : 20 - 60W/M

Luminaire Efficacy : 110lm/W

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type : Linear Rigid Module VS

Diffuser : Anti yellowing PMMA

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty : 5 Years

Life Time : 50,000hrs at ta 25°C

(L80/B10)

Fields of Application:

Retail


Education

Galleries hotels

Living spaces

Installation Method:

Suspended



Wattage(W)/M :	20	40	60	Customized		
Finish :	White(W)	Black(B)	Silver(S)	Customized(C)		
Kelvin* :	3000K	4000K	6000K	6500K	Tunable	
Beam Angle :	120°					
CRI :	80+	90+				
Driver :	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth	
Diameter :	1000	1400	2000	2050	3600	Customized

*Special Color & Finish on request

Product Code (964807560):


Wattage/M	Lumens(LM)	Dimension(W x H) mm
20	2200LM	80 x 75
40	4400LM	80 x 75
60	6600LM	80 x 75

*Luminous flux value is calculated for 4000K and CRI>80.

*Above mentioned wattages can be customized according to designed requirement.

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 964807560 30K 120D 8 1 W 1

CCT	Beam Angle	CRI	Driver	Finish	Diameter
30K - 3000K	120D -	8-	1 - ON/OFF	W-White	1000
40K - 4000K	120°	>80	2 - 0/1-10V	B-Black	1400
60K - 6000K		9-	3 - DALI	S-Silver	2000
65K - 6500K		>90	4 - Phase	C-	2050
TuK -			Dimming	Customized	3600
Tunable			5 - Bluetooth		Customized

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C