



ROCKET



Description:

ROCKET is a Linear outdoor lighting fixtures designed to be installed flush with the ground surface, providing subtle and aesthetically pleasing illumination.

These lights typically have a linear or elongated shape, allowing them to seamlessly blend into pathways, driveways, or other outdoor areas. Linear inground lights often feature durable and weather-resistant materials to withstand outdoor conditions.

Toughened glass surface, with high hardness, not easy to break. It comes with different CCT and C5 Marine Grade Coating, this family is a perfect solution to the requirement.

Any RAL Color and length can be customized 250mm, 500mm, 750mm, 1.5mtr. They are commonly used for accentuating architectural features, guiding pathways, or creating ambiance in outdoor spaces.

Product Specifications:

Housing : Die cast Aluminum
Glass : Tempered glass
No. of LEDs : 48 LEDs
Gasket: Molding shaped silicone seal
Accessory: Side cover
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Surface Mounted

Technical Specifications:

Wattage: 120W
Voltage: DC24V / AC100V-265V
Frequency: 50-60Hz
Light Source: OSRAM/EPISTAR/CREE
Lumen: 75lm/W
Mac Adam: 3 Step
Safety Class: III
Working Temperature:-25°C to 60°C
Life Time: 50,000hrs (L80/B10) at 35°C
Humidity : <95%
Warranty: 5 Years

Parameter:


Wattage(W)	:	120W
Finish	:	Black (B) / Grey (G)
Kelvin*	:	2700K / 3000K / 4000K / 6500K
Beam Angle	:	3° / 5°
CRI	:	80+
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut / Bluetooth

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5490521	120-120W	27-2700K	D-24VDC	3-3°	B-Black	1-ON/OFF
		30-3000K		5-5°	G-Grey	2-DALI
		40-4000K				3-0/1-10V
		65-6500K				4-Phase cut
						5-Bluetooth

Ex: Order Code: 549052112027D'3B1

Photometric:



Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5490521	120-120W	27-2700K	A - 100V-265VAC	3-3°	B-Black	1-ON/OFF
		30-3000K		5-5°	G-Grey	2-DALI
		40-4000K				3-0/1-10V
		65-6500K				

Ex: Order Code: 549052112027A'3B1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C