



ROCKET



Description:

ROCKET is a Linear outdoor lighting fixtures designed to be installed flush with the ground surface, providing subtle and aesthetically pleasing illumination. These lights typically have a linear or elongated shape, allowing them to seamlessly blend into pathways, driveways, or other outdoor areas. Linear inground lights often feature durable and weather-resistant materials to withstand outdoor conditions. Toughened glass surface, with high hardness, not easy to break. It comes with different CCT and C5 Marine Grade Coating, this family is a perfect solution to the requirement. Any RAL Color and length can be customized 250mm, 500mm, 750mm, 1.5mtr. They are commonly used for accentuating architectural features, guiding pathways, or creating ambiance in outdoor spaces.

Product Specifications:

- Housing : Die cast Aluminum
- Glass : Tempered glass
- No. of LEDs : 72 LEDs
- Gasket: Molding shaped silicone seal
- Accessory: Side cover
- Lens/Reflector : Optical lens (efficiency>90%)
- Power Cable: 0.5 mt. power cable included
- Driver : High efficiency, low flicker driver
- Installation Type: Surface Mounted

Technical Specifications:

- Wattage: 180W
- Voltage: DC24V / AC100V-265V
- Frequency: 50-60Hz
- Light Source: OSRAM/EPISTAR/CREE
- Lumen: 75lm/W
- Mac Adam: 3 Step
- Safety Class: III
- Working Temperature:-25°C to 60°C
- Life Time: 50,000hrs (L80/B10) at 35°C
- Humidity : <95%
- Warranty: 5 Years

Parameter:


Wattage(W)	:	180W
Finish	:	Black (B) / Grey (G)
Kelvin*	:	1700K / 2700K / 3000K / 4000K / 6500K
Beam Angle	:	3° / 5°
CRI	:	80+
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut / Bluetooth

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5494524	180-180W	17-1700K	D-24VDC	3-3°	B-Black	1-ON/OFF
		27-2700K		5-5°	G-Grey	2-DALI
		30-3000K				3-0/1-10V
		40-4000K				4-Phase cut
		65-6500K				5-Bluetooth

Ex: Order Code: 549452418017D'3B1

Photometric:



Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5494524	180-180W	17-1700K	A - 100V-265VAC	3-3°	B-Black	1-ON/OFF
		27-2700K		5-5°	G-Grey	2-DALI
		30-3000K				3-0/1-10V
		40-4000K				
		65-6500K				

Ex: Order Code: 549452418017A'3B1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C