




ROCKET



LED



Description:

ROCKET is a Linear outdoor lighting fixtures designed to be installed flush with the ground surface, providing subtle and aesthetically pleasing illumination.

These lights typically have a linear or elongated shape, allowing them to seamlessly blend into pathways, driveways, or other outdoor areas. Linear inground lights often feature durable and weather-resistant materials to withstand outdoor conditions.

Toughened glass surface, with high hardness, not easy to break. It comes with different CCT and C5 Marine Grade Coating, this family is a perfect solution to the requirement.

Any RAL Color and length can be customized 250mm, 500mm, 750mm, 1.5mtr. They are commonly used for accentuating architectural features, guiding pathways, or creating ambiance in outdoor spaces.

Product Specifications:

Housing : Die cast Aluminum

Glass : Tempered glass

No. of LEDs : 96 LEDs

Gasket: Molding shaped silicone seal

Accessory: Side cover

Lens/Reflector : Optical lens (efficiency>90%)

Power Cable: 0.5 mt. power cable included

Driver : High efficiency, low flicker driver

Installation Type: Surface Mounted

Technical Specifications:

Wattage: 240W

Voltage: DC24V / AC100V-265V

Frequency: 50-60Hz

Light Source: OSRAM/EPISTAR/CREE

Lumen: 50lm/W

Mac Adam: 3 Step

Safety Class: III

Working Temperature:-25°C to 60°C

Life Time: 50,000hrs (L80/B10) at 35°C

Humidity : <95%

Warranty: 5 Years

Parameter:

Wattage(W) : 240W

Finish : Black (B) / Grey (G)


Kelvin* : RGB / RGB DMX / RGBW / RGBW DMX

Beam Angle : 15°

CRI : 80+

Control Mode : ON/OFF / DALI / DMX

Photometric:



Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5498069	240-240W	92-RGB	D-24VDC	15-15°	B-Black	1-ON/OFF
		93-RGB DMX			G-Grey	2-DALI
		82-RGBW				3-DMX
		83-RGBW DMX				

549806924092D'15B

Ex: Order Code: 1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5498069	240-240W	92-RGB	A - 100V-265VAC	15-15°	B-Black	1-ON/OFF
		93-RGB DMX			G-Grey	2-DALI
		82-RGBW				3-DMX
		83-RGBW DMX				

Ex: Order Code: 549806924092A'15B1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C