

## RUSTIC



### Description:

RUSTIC is an outdoor down light wall lamp with special optical design.

Constructed from high-quality ADC-12 die-cast aluminum with a durable painted finish, toughened glass, and stainless steel hexagonal socket screws for enhanced corrosion resistance and longevity.

Equipped with multiple-angle lenses, the fixture allows precise adjustment of light direction and distribution to suit different lighting requirements—whether focused illumination for specific areas or wide, diffused lighting for larger spaces. The addition of polarized optics enhances control over light direction, minimizing glare and reflection while creating a more comfortable and visually balanced environment.

Ideal for architectural, commercial, and residential applications requiring both performance and design elegance.

### Product Specifications:

Housing : Die cast Aluminium  
 Glass : Toughened Glass  
 Diffuser : Clear Glass  
 Coating : Powder Coating  
 Screws : Stainless Steel  
 Gasket: Moulding shaped silicone seal  
 Lens/Reflector : Optical lens (efficiency>90%)  
 Power Cable: 0.5 mt. power cable included  
 Driver : High efficiency, low flicker driver  
 Installation Type: Surface mounted  
 Adjustable: No

### Technical Specifications:

Wattage: 3.5-11W  
 Voltage: 220-240VAC  
 Frequency: 50-60Hz  
 Light Source: OSRAM/EPISTAR/CREE  
 Lumen: 50lm/W  
 Mac Adam: 3 Step  
 Safety Class: I  
 Working Temperature:-20°C to 50°C  
 Life Time: 50,000hrs (L80/B10) at 25°C  
 Warranty: 5 Years

### Parameter:

Wattage(W)	:	3.5W / 6W / 8W / 11W
Finish	:	Black (B) / Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	15° / 23° / 38° / 50° / 35°*70° / 40°*40° / 60°*60°
CRI	:	90+
Control Mode	:	ON/OFF / DALI / 0 / 1-10V
Type	:	Type A / Type B / Type C / Type D

### Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

### Order Code:


Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540198	03 - 3.5W (1*3.5W)	27-2700K	A-220-240VAC	15 - 15°	B-Black	1-ON/OFF
	06 - 6W (2*3W)	30-3000K		23 - 23°	C-Customized	2-DALI
	08 - 8W (3*2.6W)	40-4000K		38 - 38°		3-0/1-10V
	11 - 11W (6*1.8W)	60-6000K		50 - 50°		

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C


35\*70 - 35°\*70°  
40\*40 - 40°\*40°  
60°\*60° - 60°\*60°

Ex: Order Code: 5401980327A'15B1


**Dimensions :**




**Type A**



**Type B**



**Type C**



**Type D**

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C