

RYLO



Description:

RYLO is a minimalist Wall washer, equipped with a 6063 Aluminum rotating damping bracket with locking function and patented design for secure, adjustable installation. The toughened glass surface has high hardness and is not easy to break.

Available with different CCT options, C5 Marine Grade Coating, Slotted baffle plate, screw type baffle plate, anti-drop protection cable, adjustable bracket fixing screw, breather valve, short bracket this family is a perfect solution to a wide range of project requirements.

Lengths can be customized to 250mm, 500mm, 750mm, and 1.5m.

These fixtures are commonly used for accentuating architectural features, guiding pathways, or creating ambiance in outdoor spaces.

Product Specifications:

Housing : 6063 Aluminum
 Glass : Tempered glass
 Coating : Powder Coating
 No. of LEDs : 24 LEDs
 Light Source: CREE / OSRAM / LumiLEDs
 Driver : VS / Meanwell / Boke
 Gasket: Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Surface Mounted
 Adjustable : Yes

Technical Specifications:

Wattage: 12 - 36W
 Voltage: 24VDC / 220-240VAC
 Frequency: 50-60Hz
 Lumen: 83lm/W
 Mac Adam: 3 Step
 Safety Class: III
 Working Temperature: -40°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Humidity : <95%
 Warranty: 5 Years

Parameter:

Wattage(W)	: 12W / 24W / 36W
Finish	: RAL 9005 (B) / RAL 9010 (W) / RAL 7138 (G)
Kelvin*	: 2700K / 3000K / 4000K / 6000K / RGB / RGBW
Beam Angle	: 12° / 24° / 30° / 45° / 60° / 10*25° / 10*65° / 15*30° / 20*40° / 20*60°
CRI	: 80+ 90+
Control Mode	: ON/OFF / DALI / DMX

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5424283	12 - 12W (500mm)	27 - 2700K	D - 24VDC	12-12°	B - RAL 9005	1-ON/OFF
	24 - 24W (1220mm)	30 - 3000K		24-24°	W - RAL 9010	
	36 - 36W (2000mm)	40 - 4000K		30-30°	G - RAL 7138	
		60 - 6000K		45-45°		
		82-RGB		60 - 60°		
		83-RGB DMX		10*25 - 10*25°		
		92-RGBW		10*65 - 10*65°		
		93-RGBW DMX		15*30 - 15*30°		
				20*40 - 20*40°		
				20*60 - 20*60°		

Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5424283	12 - 12W (500mm)	27 - 2700K	A - 220-240VAC	12-12°	B - RAL 9005	1-ON/OFF
	24 - 24W (1220mm)	30 - 3000K		24-24°	W - RAL 9010	2- DALI
	36 - 36W (2000mm)	40 - 4000K		30-30°	G - RAL 7138	
		60 - 6000K		45-45°		
				60 - 60°		
				10*25 - 10°*25°		
				10*65 - 10°*65°		
				15*30 - 15°*30°		
				20*40 - 20°*40°		
				20*60 - 20°*60°		

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C