



SAFE'S







A** LED 🗗 🔞 🦝 💲 🌼 🖒 LM-80 🚅 🖍 Ricker















Description:

SAFE'S is a step lamp with special optical design, and with simple shape and rich texture. It is composed of die-casting aluminum parts, PC lenses and engineering plastic parts. The special surface treatment process for outdoor lamps makes the lamps have good weather resistance.

Its a step light series divided is divided into square and rectangular shapes. The unique optical design makes the light outlet of the lamp small.

With the micro structure design of the light outlet, the lamp has no glare, with large light coverage and high uniformity.

Control Mode: 1-10V dimming and Dali 2 dimming.

It can be applicable indoor and outdoor lighting purpose, wall path lighting, etc.

Product Specifications:

Housing: Die cast Aluminium grey

Diffuser: Clear Glass

Gasket: Moulding shaped silicone seal Lens/Reflector: Optical lens (efficiency>90%) Power Cable: 0.5 mt. power cable included Driver: High efficiency, low flicker driver

Installation Type: Recessed

Adjustable: No

Technical Specifications:

Wattage: 4W


Voltage: 220-240VAC Frequency: 50-60Hz

Light Source: OSRAM/EPISTAR/CREE

Lumen: 75lm/W Mac Adam: 3 Step Safety Class: II

Working Temperature: -20°C to 55°C Life Time: 50,000hrs (L80/B10) at 35°C

Warranty: 5 Years



Standards:

EN 60598-1 EN 60598-2-2 EN 60598-3-2

EN 60598-3-3

Parameter:

| Wattage(W) | : | 4W |
|------------|---|---|
| Finish | : | Black (B) / Silver (S) / Customized (C) |
| Kelvin* | : | 2700K/3000K/4000K |
| Beam Angle | : | 30°/50° |
| CRI | : | 80 |

Order Code:

Control Mode:

| Product Code | Wattage | CCT | Voltage | Beam Ang | le Finish | Control Mode | |
|--------------|---------|----------|--------------|----------|---------------------------------|--------------|--|
| 540112 | 4 - 4W | 27-2700K | A-220-240VAC | 30-30° | B-Black | 1-ON/OFF | |
| | | 30-3000K | | 50-50° | S-Silver | 2-DALI | |
| | | 40-4000K | | | C-Customized | 3-0/1-10V | |
| | | | | E | Ex: Order Code: 540112427A'30B1 | | |

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

ON/OFF / DALI / 0 / 1-10V