



SCUD



**Description:**

SCUD Bollard a modern outdoor bollard light with a sleek, angular design. It features a rectangular, black metal body with a right-angled top section where the light would likely be emitted, providing downlighting for high efficiency and vandal resistance with anti-glare plate . Easy access to LED and driver via a removable head.

Tamper proof fixings for increased vandal resistance, weather-resistant housings suitable for outdoor use. Excellent heat dissipation.

It include features such as corrosion resistance , dustproof, anodized and polished, sand blasted, not easy to rust and fade.

It comes with different CCT LED sources and various beam angles this family is a perfect solution to the requirement.

This type of fixture is often used for pathway, landscape lighting, Parking lots , Park And Garden due to its minimalist, contemporary style.

**Product Specifications:**

- Housing : Die cast Aluminium
- Reflector : Anodised Aluminium reflector
- Diffuser : Tempered Glass
- Coating: Powder Coating
- Gasket: Moulding shaped silicone seal
- Power Cable: 0.5 mtr. power cable included
- Driver : High efficiency, low flicker driver
- Installation Type: Surface Mounted
- Adjustable: No

**Technical Specifications:**

- Wattage: 7-10W
- Voltage: 220-240V AC
- Frequency: 50-60Hz
- Light Source: Philips 3030 SMD
- Lumen: 100lm/W
- Mac Adam: 4 Step
- Safety Class: I
- Working Temperature:-20°C to 55°C
- Life Time: 50,000hrs (L80/B10) at 35°C
- Warranty: 5 Years

**Parameter:**


Wattage(W)	:	7W / 10W
Finish	:	Black (B) / Grey (G) / Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 5000K / 6000K
Beam Angle	:	120° / Symmetric / Asymmetric / Double Asymmetric
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V

**Order Code:**

Product Code	Wattage CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
547	07-7W	27-2700K	A-220-240VAC	120-120°	G-Grey 1-ON/OFF
	10-10W	30-3000K		S-Symmetric	B-Black 2-DALI
		40-4000K		AS-Asymmetric	C-Customized 3-0/1-10V
		50-5000K		DAs-Double Asymmetric	
		60-6000K			

**Ex: Order Code:** 5470727A'120G1

**Photometric :**



**Standards :**

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C