

SHOW L



Description:

SHOW L is a modern bollard light embodies a perfect balance of minimalist design and advanced engineering, seamlessly integrating into diverse outdoor architectural settings. Crafted with a die-cast aluminum head and extruded aluminum body, it offers durability with a refined, high-end textured finish achieved through premium surface treatments and coatings. The professional optical design ensures exceptional performance—featuring a 20° tilted PCB and 60° wide-angle polarization for optimal light spread. Its asymmetrical distribution allows a single fixture to effectively cover up to 8 x 4 meters, making it both efficient and versatile. Dark Sky compliant, it prevents uplighting and minimizes light pollution, fostering a more eco-friendly and sustainable outdoor environment. With its sleek form and precise illumination, this bollard light not only enhances visibility but also elevates the ambiance of modern outdoor spaces. Main uses in courtyards, gardens, park paths, commercial buildings, corporate headquarters, passages of public recreational areas, etc.

Available Height Options: 350mm and 750mm

Product Specifications:

Housing : Die cast Aluminium
Diffuser : Polycarbonate
Coating: Powder Coating
Net Weight : 1.7KG
Motion Sensor : Optional
Gasket: Moulding shaped silicone seal
Power Cable: 0.5 mtr. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Surface Mounted
Adjustable: No
Warranty: 5 Years

Technical Specifications:

Wattage: 5 - 12W
Voltage: 200-240V AC
Frequency: 50-60Hz
Light Source: Bridgelux / OSRAM
Lumen: 90lm/W
Mac Adam: 3 Step
Safety Class: III
Working Temperature: -30°C to 45°C
Life Time: 50,000hrs (L70/B50) at 35°C

Parameter:


Wattage(W)	:	5W / 12W
Finish	:	Black (B) / White (W) / Silver (S) / Grey (G)
Kelvin*	:	2700K/ 3000K / 4000K
Optics	:	Asymmetrical
CRI	:	80+
Control Mode	:	ON/OFF / DALI

Order Code:

Product Code	Wattage	CCT	Voltage(AC)	Optics	Finish	Control Mode
547135	5 - 5W (350mm)	27-2700K	A-200-240VAC	AS - Asymmetrical	B-Black	1-ON/OFF
	12 - 12W (750mm)	30-3000K			W-White	2-DALI
		40-4000K			S-Silver	
					G-Grey	

Ex: Order Code: 547135527AASB1

Photometric :



Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C