


SILK



Features:

SILK is fixed Spot Light made of high-quality of die-cast aluminum with a solvent-free powder coating for durability and eco-friendliness.

The robust housing is designed to maintain optimal LED performance while preserving a sleek and minimal architectural appearance.

And also, with the refined optical lens for precise, glare-controlled illumination.

Its deep focal length and anti-glare trim design further enhance visual comfort by minimizing light spill and glare, making it ideal for precision lighting.

Homogenous, well-balance light dispersing, no shadow.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50/60Hz.

Wattage: 3W

Efficiency: 55lm/W

High efficiency, low flicker driver

3 STEP Mac Adam

Lamp Type: COB

Chip Brand: VS / Citizen / CREE

Driver Brand: VS / Tridonic / OSRAM

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Lifetime 50,000hrs at a 25°C(L80/B10)

Fields of Application:

Retail

Education

Galleries hotels

Living spaces

Museums

Restaurants

Painting Exhibitions

Theaters

Installation Method:

Recessed

Wattage(W)	:	3				
Finish	:	White(W)	Black(B)			
Kelvin*	:	2700K	3000K	3500K	4000K	5000K
Beam Angle	:	24°				
CRI	:	90+				
Driver	:	ON/OFF	DALI	Phase Dimming	0/1-10V	


*Special Color and Finish on request

Product Code (96702803):

Wattage	Lumens(lm)	Dimension (ØxH) mm	Cut Out  (mm)
3	165LM	28x72	25

*Luminous flux value is calculated for 4000K CRI>90, 3 STEP Mac Adam.

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C

- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: <u>96702803</u> <u>27K</u> <u>24D</u> <u>9</u> <u>1</u> <u>W</u>				
CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	24D - 24°	9->90	1 - ON/OFF	W-White
30K - 3000K			2 - DALI	B-Black
35K - 3500K			3 - Phase Dimming	
40K - 4000K			4 - 0/1-10V	
50K - 5000K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C