


SILLIN



Features:

Cylindrical downlights designed with a deep reflector to be a low glare value.
Die Cast Aluminum body with different RAL finish, Solvent free power coating, and PMMA optics lens.
Antiglare reflector with excellent light dispersion.
Easy to do the installation.
High light Transmissivity.
Homogenous, well-balanced, no shadow.

Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.
Wattage: 30-35W
High Lumen: 100lm/W
3 STEP Mac Adam
High efficiency, low flicker driver
Lamp Type: COB
Light Source: CREE/ CITIZEN
Driver Brand: Vossloh Schwabe / Tridonic
Operating Temperature: -20°C to 45°C
Glow Wire Test 850° C
Warranty: 5 Years
Life Time: 50,000hrs at ta 25°C (L80/B10)

Fields of Application:

Retail
Galleries hotels
Living spaces
Conference rooms
Counters
Restaurants

Installation Method:

Surface Mounted.

Wattage(W)	:	30	35				
Finish	:	White(W)	Black(B)	Gray(G)			
Kelvin*	:	2700K	3000K	3500K	4000K	5000K	6500K
Beam Angle	:	20°	40°	60°			
CRI	:	80+	90+				
Driver	:	ON/OFF	0/1-10V	DALI	Casambi		




*Special Color & Finish on request

Product Code (99814035):

Wattage	Lumens(lm)	Dimension(ØxH) mm
30	3000LM	140x150
35	3500LM	140x150

*Luminous flux value is calculated for 4000K CRI>80, 3 STEP Mac Adam.

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 99814035 27K 20D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	20D - 20°	8->80	1 - ON/OFF	W-White
30K - 3000K	40D - 40°	9->90	2 - 0/1-10V	B-Black
35K - 3500K	60D - 60°		3 - DALI	G-Gray
40K - 4000K			4 - Casambi	
50K - 5000K				
65K - 6500K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C