



SINO'F



Description:

SINO is an Inground wood floor thin and small wattage light typically feature durable, weather-resistant housings suitable for outdoor use. Excellent heat dissipation.

It include features such as corrosion resistance , dustproof, anodized and polished, sandblasted, not easy to rust and fade.

Toughened glass surface, with high hardness, not easy to break.

It comes with different CCT and R/G/B LED sources and various beam angles this family is a perfect solution to the requirement.

It has very wide application like For Living Rooms and Hallways, Staircases, Outdoor Decks and Patios, Retail Stores, Office Spaces, Exhibition and Gallery Spaces all types for floors.

Product Specifications:

Front cover : Stainless Steel SUS 316
Housing : Die cast aluminium Grey
Coating: Powder Coating
Glass : Tempered glass
Gasket: Molding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Inground
Adjustable: No

Technical Specifications:

Wattage: 2- 2.5W
Voltage: DC24V / 220-240V AC
Frequency: 50-60Hz
Light Source: OSRAM/EPISTAR/CREE
Lumen: 100lm/W
Mac Adam: 3 Step
Safety Class: III / II
Working Temperature: -20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years


Parameter:

Wattage(W)	:	2W / 2.5W
Finish	:	Stainless Steel SUS 316 (SS)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K / RGB
Beam Angle	:	120°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut / DMX
Type	:	Round (R) / Square (S)

Order Code:

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
544118	02-2W(6X SMD 2835)	27-2700K	D-24VDC	120 - 120°	SS-Stainless Steel 316	1-ON/OFF
	03-2.5W(12X SMD 2835)	30-3000K				2-DALI
		40-4000K				3-0/1-10V
		60-6000K				4-Phase cut
		92-RGB				5-DMX

Photometric :



Standard :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Ex: Order Code: 5441180227D'120SS1

Product Code	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
544118	03-2.5W(12X SMD 2835)	27-2700K	A-220-240VAC	120 - 120°	SS-Stainless Steel 316	1-ON/OFF
		30-3000K				2-DALI
		40-4000K				3-0/1-10V
		60-6000K				4-Phase cut

Ex: Order Code: 5441180327A'120SS1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C