



## SINO'F



### Description:

SINO is an Inground wood floor thin and small wattage light typically feature durable, weather-resistant housings suitable for outdoor use. Excellent heat dissipation.

It include features such as corrosion resistance , dustproof, anodized and polished, sandblasted, not easy to rust and fade.

Toughened glass surface, with high hardness, not easy to break.

It comes with different CCT and R/G/B LED sources and various beam angles this family is a perfect solution to the requirement.

It has very wide application like For Living Rooms and Hallways, Staircases, Outdoor Decks and Patios, Retail Stores, Office Spaces, Exhibition and Gallery Spaces all types for floors.

### Product Specifications:

Front cover : Stainless Steel SUS 316  
Housing : Die cast aluminium Grey  
Coating: Powder Coating  
Glass : Tempered glass  
Gasket: Molding shaped silicone seal  
Lens/Reflector : Optical lens (efficiency>90%)  
Power Cable: 0.5 mt. power cable included  
Driver : High efficiency, low flicker driver  
Installation Type: Inground  
Adjustable: No

### Technical Specifications:

Wattage:5- 7W  
Voltage: DC24V / 220-240V AC  
Frequency: 50-60Hz  
Light Source: OSRAM/EPISTAR/CREE  
Lumen: 100lm/W  
Mac Adam: 3 Step  
Safety Class: III / II  
Working Temperature:-20°C to 55°C  
Life Time: 50,000hrs (L80/B10) at 35°C  
Warranty: 5 Years


### Parameter:

Wattage(W)	:	5W / 6W / 7W
Finish	:	Stainless Steel SUS 316 (SS)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K / RGB / RGBW
Beam Angle	:	120°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut / DMX
Type	:	Round ( R ) / Square (S)

### Order Code:

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
544117	05-5W(18X SMD 5050 )	27-2700K	D-24VDC	120 - 120°	SS-Stainless Steel 316	1-ON/OFF
	06-6W(36X SMD 2835)	30-3000K				2-DALI
	07-7W(18XSMD 5050)	40-4000K				3-0/1-10V
		60-6000K				4-Phase cut
		92-RGB				5-DMX
		93-RGB DMX				

### Photometric :



### Standard :

EN 60598-1  
EN 60598-2-2  
EN 60598-3-2  
EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C

82-RGBW  
83-RGBW  
DMX

**Ex: Order Code:** 5441170527D'120SS1

Product Code	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
544117	06-6W(36X SMD 2835)	27-2700K	A-220-240VAC	120 - 120°	SS-Stainless Steel 316	1-ON/OFF
		30-3000K				2-DALI
		40-4000K				3-0/1-10V
		60-6000K				4-Phase cut

**Ex: Order Code:** 5441170627A'120SS1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C