

SKATE



Description:

SKATE is a outdoor linear LED light fixture. It appears to be designed for architectural use, featuring a long, narrow shape with mounting brackets and connectors on both ends.

It include features such as corrosion resistance , dustproof, anodized and polished, sandblasted, not easy to rust and fade.

Toughened glass surface, with high hardness, not easy to break.

Length options: 250mm , 500mm , 750mm , 1mtr , 1.2mtr , can be customized on request.

The number of lenses within the system changes based on the selected length, ensuring optimal performance and functionality for each configuration.

They are commonly used in architectural lighting to enhance the aesthetics of buildings, highlight textures, and create visually appealing lighting effects.

Product Specifications:

Housing : Die cast Aluminium
 Coating: Powder Coating
 Glass : Tempered glass
 Gasket: Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Surface Mounted
 Adjustable: No
 Warranty: 5 Years

Technical Specifications:

Wattage: 10- 12W
 Voltage: DC24V
 Frequency: 50-60Hz
 Light Source: OSRAM/EPISTAR/CREE
 No. of pixel : 8 Pixel/M
 UCs512 IC for DMX
 Lumen: 100lm/W
 Mac Adam: 3 Step
 Safety Class: III
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C

Parameter:


Wattage(W)	:	10W / 12W
Finish	:	Grey (G) / Customized (C)
Kelvin*	:	1800K~6500K / 2700K / 3000K / 4000K / 6000K / R / G / B / RGB / RGBW
Beam Angle	:	120°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut / DMX / SPI

Order Code:

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
5543028	10-10W	27-2700K	D-24VDC	120-120°	G-Grey	1-ON/OFF
		30-3000K				2-DALI
	40-4000K	3-0/1-10V				
	60-6000K	4-Phase Cut				
	92-RGB	5-DMX				
	93-RGB DMX	6-SPI				
12-12W	82-RGBW					
	83-RGBW DMX					
	18-65-18K-65K					

Ex: Order Code: 55430281027D'120G1

Photometric:



Standards:

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C