




## SKY



### Features:

Sky Downlight Die Cast Aluminum body, black solvent free power coating.  
Excellent heat dissipation with aluminum outer ring matt black/white finished.  
Polycarbonate frosted cover, Anti-UV and Anti-yellow changing.  
Osram SMD2835 with a great thermal conductivity.  
Spring Clips Metal body, strongest strength, Easy to do the recessed installation.

### Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.  
Wattage: 15 - 20 W  
High Lumen: 105lm/W  
3 STEP Mac Adam  
High efficiency, low flicker driver  
Lamp Type: SMD  
Operating Temperature: -25°C to +50°C  
Glow Wire Test 850°C  
Warranty: 5 Years  
Life Time: 50,000hrs at ta 25°C  
(L80/B10)

### Fields of Application:

Retail  
Galleries hotels  
Living spaces  
Conference rooms  
Counters  
Restaurants

### Installation Method:

Recessed

Wattage(W)	:	15	20			
Finish	:	White(W)	Black(B)			
Kelvin*	:	3000K	4000K	5000K	5700K	6500K
Beam Angle	:	120°				
CRI	:	80+	90+			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth


\*Special Color & Finish on request

### Product Code (96816020):

Wattage	Lumens(lm)	Dimension(Ø x H) mm	Cut Out (mm)
15	1575LM	160X62	140
20	2100LM	160X62	140

\*Luminous flux value is calculated for 4000K CRI>80

### Photometric:



### Standards

EN 60598-1  
EN 60598-2-2  
EN 60598-2-22  
EN 60598-3-2  
EN 60598-3-3

Order Code Ex: 96816020 30K 120D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	120D - 120°	8->80	1 - ON/OFF	W-White
40K - 4000K		9->90	2 - 0/1-10V	B-Black
50K - 5000K			3 - DALI	
57K - 5700K			4 - Phase Dimming	
65K - 6500K			5 - Bluetooth	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C