


SLOVE



Description:

SLOVE Inground Light is a durable and versatile outdoor fixture. It features a 316 stainless steel top with tempered safety glass and supports loads up to 2000kg, making it suitable for high-traffic areas. The housing is made from die-cast aluminum or CNC-machined 6061 aluminum with a hard anodized finish for strong corrosion resistance. It includes an adjustable beam angle (+30° to -15°) that can be modified externally without opening the fixture, along with a pre-buried installation sleeve for easy setup. Multiple anti-glare options such as reflector, louver, and lens combinations are available. A wall washer version is also offered for uniform vertical illumination with minimal glare.

Product Specifications:

Front Cover : Stainless Steel
 Housing : Die Cast Aluminum
 Coating: Powder Coating
 Diffuser : Tempered glass
 Net Weight : 0.27KG
 Gasket : Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Inground
 Adjustable: Yes

Technical Specifications:

Wattage: 3W
 Voltage: 24VDC
 Frequency: 50-60Hz
 Light Source: OSRAM / CREE
 Mac Adam: 3 Step
 Safety Class: III
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 25°C
 Warranty: 5 Years

Parameter:

Wattage(W)	: 3W
Finish	: Stainless Steel (SS)
Kelvin*	: 2700K/ 3000K / 4000K / 6000K / RGB / RGBW
Beam Angle	: 9°/ 18°/ 22°/ 40°/ 52°/ 10*40°/ 10*60°/ 15*60°/ 20*60°
Lumens (with louver)	: 78lm/ 113lm/ 93lm/ 172lm/ 175lm/ 111lm/ 122lm/ 131lm/ 125lm
Lumens (without louver)	: 287lm/ 281lm/ 281lm/ 281lm/ 281lm/ 271lm/ 223lm/ 243lm/ 261lm/ 249lm
CRI	: 80+
Control Mode	: ON/OFF / DALI / DMX
Lens Types	: Type A / Type B / Type C / Type D / Type E / Type F

*For each beam angle, the corresponding lumen output is provided both with and without louver.

Order Code:

Product Code	Wattage CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
544049	03 - 3W 27-2700K	D - 24VDC	09 - 09°	SS - Stainless Steel	1-ON/OFF
	30-3000K		18 - 18°		2-DALI

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

40- 4000K
60-6000K
82-RGB
83-RGB DMX
92-RGBW
93-RGBW DMX

22 - 22°
40-40°
52-52°
10*40-10*40°
10*60-10*60°
15*60-15*60°
20*60-20*60°

3-DMX

Ex: Order Code: 5440490327D'09SS1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C