


SLOVE



210



177

196



**Description:**

SLOVE Inground Light is a durable and versatile outdoor fixture. It features a 316 stainless steel top with tempered safety glass and supports loads up to 2000kg, making it suitable for high-traffic areas. The housing is made from die-cast aluminum or CNC-machined 6061 aluminum with a hard anodized finish for strong corrosion resistance. It includes an adjustable beam angle (+30° to -15°) that can be modified externally without opening the fixture, along with a pre-buried installation sleeve for easy setup. Multiple anti-glare options such as reflector, louver, and lens combinations are available. A wall washer version is also offered for uniform vertical illumination with minimal glare.

**Product Specifications:**

Front Cover : Stainless Steel  
 Housing : Die Cast Aluminum  
 Coating: Powder Coating  
 Diffuser : Tempered glass  
 Net Weight : 3.4KG  
 Gasket : Molding shaped silicone seal  
 Lens/Reflector : Optical lens (efficiency>90%)  
 Power Cable: 0.5 mt. power cable included  
 Driver : High efficiency, low flicker driver  
 Installation Type: Inground  
 Adjustable: Yes

**Technical Specifications:**

Wattage: 36W  
 Voltage: 24VDC / 220-240VAC  
 Frequency: 50-60Hz  
 Light Source: OSRAM / CREE  
 Mac Adam: 3 Step  
 Safety Class: III  
 Working Temperature:-20°C to 55°C  
 Life Time: 50,000hrs (L80/B10) at 25°C  
 Warranty: 5 Years

**Parameter:**

Wattage(W)	:	36W
Finish	:	Stainless Steel (SS)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K / RGB / RGBW
Beam Angle	:	3°/ 9°/ 12°/ 20°/ 40°/ 50°/ 10*40°/ 10*60°/ 15*60°/ 20*60°
Lumens (with louver)	:	101lm/ 628lm/ 807lm/ 1285lm/ 2066lm/ 2098lm/ 1335lm/ 1458lm/ 1566lm/ 1494lm
Lumens (without louver)	:	672lm/ 2296lm/ 1808lm/ 1911lm/ 3374lm/ 3258lm/ 2670lm/ 2616m/ 3132lm/ 2988lm
CRI	:	80+
Control Mode	:	ON/OFF / DALI / DMX
Types	:	Type A / Type B / Type C / Type D / Type E / Type F

\*For each beam angle, the corresponding lumen output is provided both with and without louver.

**Order Code:**

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
--------------	---------	-----	-------------	------------	--------	--------------

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

544212	36 - 36W	27-2700K	D - 24VDC	03 - 03°	SS - Stainless Steel	1-ON/OFF
		30-3000K		09 - 09°		2-DALI
		40- 4000K		12 - 12°		3-DMX
		60-6000K		20 - 20°		
		82-RGB		30-30°		
		83-RGB DMX		50-50°		
		92-RGBW		10*40-10*40°		
		93-RGBW DMX		10*60-10*60°		
				15*60-15*60°		
				20*60-20*60°		

**Ex: Order Code:** 5442123627D'03SS1

Product Code	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
544212	36 - 36W	27-2700K	A - 220 - 240VAC	03 - 03°	SS - Stainless Steel	1-ON/OFF
		30-3000K		09 - 09°		2-DALI
		40- 4000K		12 - 12°		
		60-6000K		20 - 20°		
				30-30°		
				50-50°		
				10*40-10*40°		
				10*60-10*60°		
				15*60-15*60°		
				20*60-20*60°		

**Ex: Order Code:** 5442123627A'03SS1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C