


SLOVE



260



240



Description:

SLOVE Inground Light is a durable and versatile outdoor fixture. It features a 316 stainless steel top with tempered safety glass and supports loads up to 2000kg, making it suitable for high-traffic areas. The housing is made from die-cast aluminum or CNC-machined 6061 aluminum with a hard anodized finish for strong corrosion resistance. It includes an adjustable beam angle (+30° to -15°) that can be modified externally without opening the fixture, along with a pre-buried installation sleeve for easy setup. Multiple anti-glare options such as reflector, louver, and lens combinations are available. A wall washer version is also offered for uniform vertical illumination with minimal glare.

Product Specifications:

Front Cover : Stainless Steel
 Housing : Die Cast Aluminum
 Coating: Powder Coating
 Diffuser : Tempered glass
 Net Weight : 5.1KG
 Gasket : Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Inground
 Adjustable: Yes

Technical Specifications:

Wattage: 48W
 Voltage: 24VDC / 220-240VAC
 Frequency: 50-60Hz
 Light Source: OSRAM / CREE
 Mac Adam: 3 Step
 Safety Class: III
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 25°C
 Warranty: 5 Years

Parameter:

Wattage(W)	:	48W
Finish	:	Stainless Steel (SS)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K / RGB / RGBW
Beam Angle	:	3°/ 9°/ 12°/ 20°/ 40°/ 50°/ 10*40°/ 10*60°/ 15*60°/ 20*60°
Lumens (with louver)	:	304lm/ 1256lm/ 1610lm/ 2549lm/ 2754lm/ 4344lm/ 1780lm/ 944lm/ 2088lm/ 1992lm
Lumens (without louver)	:	2016lm/ 4593lm/ 3607lm/ 3814lm/ 4499lm/ 2797lm/ 3560lm/ 3888lm/ 4176lm/ 3984lm
CRI	:	80+
Control Mode	:	ON/OFF / DALI / DMX
Types	:	Type A / Type B / Type C / Type D / Type E / Type F

*For each beam angle, the corresponding lumen output is provided both with and without louver.

Order Code:

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
--------------	---------	-----	-------------	------------	--------	--------------

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

544263	48 - 48W	27-2700K	D - 24VDC	03 - 03°	SS - Stainless Steel	1-ON/OFF
		30-3000K		09 - 09°		2-DALI
		40- 4000K		12 - 12°		3-DMX
		60-6000K		20 - 20°		
		82-RGB		30-30°		
		83-RGB DMX		50-50°		
		92-RGBW		10*40-10*40°		
		93-RGBW DMX		10*60-10*60°		
				15*60-15*60°		
				20*60-20*60°		

Ex: Order Code: 5442634827D'03SS1

Product Code	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
544263	48 - 48W	27-2700K	A - 220 - 240VAC	03 - 03°	SS - Stainless Steel	1-ON/OFF
		30-3000K		09 - 09°		2-DALI
		40- 4000K		12 - 12°		
		60-6000K		20 - 20°		
				30-30°		
				50-50°		
				10*40-10*40°		
				10*60-10*60°		
				15*60-15*60°		
				20*60-20*60°		

Ex: Order Code: 5442634827A'03SS1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C