


## SNAP'C



### Description:

SNAP'C outdoor linear COB wall washer is lighting fixtures designed to provide uniform illumination along the length of a wall or other vertical surfaces.

It include features such as corrosion resistance , dustproof, anodized and polished, sandblasted, not easy to rust and fade.

Toughened glass surface, with high hardness, not easy to break.

It comes with different CCT and R/G/B LED sources and C5 Marine Grade Coating, this family is a perfect solution to the requirement.

They are commonly used in architectural lighting to enhance the aesthetics of buildings, highlight textures, and create visually appealing lighting effects

### Product Specifications:

Housing : Die cast aluminum  
 Front cover : Die cast aluminum  
 Coating: Powder Coating  
 Glass : Silver Print glass  
 Gasket: Molding shaped silicone seal  
 Lens/Reflector : Optical lens (efficiency>90%)  
 Power Cable: 0.5 mt. power cable included  
 Driver : High efficiency, low flicker driver  
 Installation Type: Surface Mounted  
 Adjustable: Yes

### Technical Specifications:

Wattage: 24W  
 Voltage: DC24V / 220-240V AC  
 Frequency: 50-60Hz  
 Light Source: OSRAM/EPISTAR/CREE  
 Lumen: 100lm/W  
 Mac Adam: 3 Step  
 Safety Class: III / II  
 Working Temperature:-20°C to 55°C  
 Life Time: 50,000hrs (L80/B10) at 35°C  
 Warranty: 5 Years

### Parameter:


Wattage(W)	:	24W
Finish	:	Grey (G) / Customized (C)
Kelvin*	:	2700K / 3000K / 4000K / 6000K / RGB / RGBW
Beam Angle	:	Symmetric 8° / 15° / 25° / 40° / 60° and Asymmetric 10*30° / 10*40° / 10*60° / 20*40° / 20*60°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut / DMX

### Order Code:

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
5425296	24C-24W(6x4W)	27-2700K	D-24VDC	8-8°	G-Gray	1-ON/OFF
		30-3000K		15-15°	C-Customize	2-DALI
		40-4000K		40-40°		3-0/1-10V
		60-6000K		10*30-10*30°		4-Phase Cut
		82-RGBW		10*40-10*40°		5-DMX
		83-RGBW DMX		20*40-20*40°		

Ex: Order Code: 542529624C27D'8G1

### Photometric:



### Standards

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Product Code	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
--------------	---------	-----	-------------	------------	--------	--------------

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C

5425296	24C-24W(6x4W)	27-2700K	A-220-240VAC	8-8°	G-Gray	1-ON/OFF
		30-3000K		40-40°	C-Customize	2-DALI
		40-4000K		10*30-10*30°		3-0/1-10V
		60-6000K		10*40-10*40°		4-Phase Cut
				20*40-20*40°		5-DMX

**Ex: Order Code:** 542529624C27A'8G1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C