


SOLLAR



Features:

Sollar series is Deep Recessed Spotlight, die cast aluminum body with PC Diffuser, product has the structure and appearance Ensures UGR<19.

Anodized Aluminum Reflector, RAL 9006, RAL 9003, RAL 9004, Solvent free power coating.

High light Transmissivity.

Homogenous, well-balanced light dispersing, no shadow.

Technical Specifications:

Input Voltage: 220- 240V AC,60/50 Hz.

Wattage: 10 - 15W

Efficiency: 115lm/w

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: COB

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at ta 25°C

(L80/B10)

Fields of Application:

Retail

Education

Galleries hotels

Living spaces

Installation Method:

Recessed

Wattage(W)	:	10	12	15		
Finish	:	Gray(G)	Black(B)	White(W)		
Kelvin*	:	3000K	4000K	5000K	6000K	6500K
Beam Angle	:	15°	24°	36°	60°	
CRI	:	80+	90+			
Driver	:	ON/OFF	0/1-10V	DALI	Bluetooth	




*Special Color & Finish on request

Product Code (96708015):

Wattage	Lumens(lm)	Dimension(Ø x H) mm	Cut Out (mm)
10	1150LM	80x75	75
12	1380LM	80x75	75
15	1725LM	80x75	75

*Luminous flux value is calculated for 4000K CRI>80

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 96708015 30K 15D 8 1 G

CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	15D - 15°	8->80	1 - ON/OFF	G-Gray
40K - 4000K	24D - 24°	9->90	2 - 0/1-10V	B-Black
50K - 5000K	36D - 36°		3 - DALI	W-White
60K - 6000K	60D - 60°		4 - Bluetooth	
65K - 6500K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C