



SOWAR'S



Features:

- SOWAR Recessed Downlight with die-cast aluminum body with heat dissipation.
- Modern kind design with easily adjust and focusable and highlight led producible or areas.
- Anti-glare cylinder type LED light.
- Easy to install and maintain.
- Fast and simple screw lock type metal ceiling base easy to install and maintain.
- High light transmissivity.

Technical Specifications:

- Input Voltage: 220-240 V AC, 50 Hz.
- Wattage: 15 W
- High Lumen: 110lm/w
- 3 STEP Mac Adam
- High efficiency, low flicker driver
- Lamp Type: COB
- Operating Temperature: -20°C to 45°C
- Glow Wire Test 850° C
- Warranty: 5 Years
- Life Time: 50,000hrs at 25°C (L80/B10)

Fields of Application:

- Retail
- Education
- Galleries hotels
- Living spaces
- Conference rooms
- Counters
- Restaurants

Installation Method:

Surface Mounted

Wattage(W)	15					
Finish	White(W)	Black(B)	Silver (S)			
Kelvin*	2700K	3000K	4000K	5000K	6000K	6500K
Beam Angle	15°	24°	36°	60°		
CRI	80+	90+				
Driver	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth	


*Special Color & Finish on request

Product Code (96806515'S):

Wattage	Lumens(lm)	Dimension(ØxH) mm
15	1620LM	65x145

*Luminous øux value is calculated for 4000K CRI>80

Photometric:



Standards

- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 96806515'S 27K 15D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	15D - 15°	8->80	1 - ON/OFF	W-White
30K - 3000K	24D - 24°	9->90	2 - 0/1-10V	B-Black
40K - 4000K	36D - 36°		3 - DALI	S-Silver
50K - 5000K	60D - 60°		4 - Phase Dimming	
60K - 6000K			5 - Bluetooth	
65K - 6500K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C