


## SPLASH



### Description:

SPLASH outdoor linear wall washer is lighting fixtures designed to provide uniform illumination along the length of a wall or other vertical surfaces. It include features such as corrosion resistance , dustproof, anodized and polished, sandblasted, not easy to rust and fade. Toughened glass surface, with high hardness, not easy to break. This lighting fixture is available in two lengths: 500 mm and 1000 mm. The number of lenses within the system changes based on the selected length, ensuring optimal performance and functionality for each configuration. They are commonly used in architectural lighting to enhance the aesthetics of buildings, highlight textures, and create visually appealing lighting effects.

### Product Specifications:

Housing : Die cast aluminum  
 Front cover : Die cast aluminum  
 Coating: Powder Coating  
 Glass : Silver Print glass  
 Gasket: Molding shaped silicone seal  
 Lens/Reflector : Optical lens (efficiency>90%)  
 Power Cable: 0.5 mt. power cable included  
 Driver : High efficiency, low flicker driver  
 Installation Type: Surface Mounted  
 Adjustable: Yes

### Technical Specifications:

Wattage: 18- 24W  
 Voltage: DC24V  
 Frequency: 50-60Hz  
 Light Source: OSRAM/EPISTAR/CREE  
 Lumen: 100lm/W  
 Mac Adam: 3 Step  
 Safety Class: III  
 Working Temperature:-20°C to 55°C  
 Life Time: 50,000hrs (L80/B10) at 35°C  
 Warranty: 5 Years

### Parameter:


Wattage(W)	:	18W / 24W
Finish	:	Grey (G) / Customized (C)
Kelvin*	:	2700K / 3000K / 4000K / 6000K / RGB / RGBW
Beam Angle	:	Symmetric 8° / 15° / 25° / 40° / 60° and Asymmetric 10*30°/10*40°/10*60° / 20*40°/20*60°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut / DMX

### Order Code:

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
5424032	18-18W(24X10.75W)	27-2700K	D-24VDC	8-8°	G-Grey	1-ON/OFF
	24-24W(24X1W)	30-3000K		15-15°	C-Customize	2-DALI
		40-4000K		40-40°		3-0/1-10V
		60-6000K		60-60°		4-Phase Cut
		92-RGB		10*30-10*30°		5-DMX
		93-RGB DMX		10*40-10*40°		
		82-RGBW		20*40-20*40°		
		83-RGBW DMX		20*60-20*60°		

**Ex: Order Code:** 54240321827D'8G1

### Photometric:



### Standards:

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C