


## STEF'V



### Description:

STEF'V is a wall recessed light fixture. It is designed to be installed flush with the wall, providing a sleek and modern look.

The light source is likely concealed within the fixture, emitting light through the specified opening in the center.

This design is often used for ambient or accent lighting in various indoor and outdoor settings. It includes features such as corrosion resistance, dustproof, anodized and polished, sandblasted, not easy to rust and fade.

It is ideal for providing ambient or accent lighting in residential or commercial spaces, such as hallways, staircases, and outdoor walkways.

### Product Specifications:

Front cover : Die cast aluminium Grey  
Housing : Die cast aluminium Grey  
Coating: Powder Coating  
Gasket: Moulding shaped silicone seal  
Lens/Reflector : Optical lens (efficiency>90%)  
Power Cable: 0.5 mt. power cable included  
Driver : High efficiency, low flicker driver  
Installation Type: Wall Recessed  
Adjustable: No

### Technical Specifications:

Wattage: 2W  
Voltage: 24VDC  
Frequency: 50-60Hz  
Light Source: OSRAM/EPISTAR/CREE  
Lumen: 100lm/W  
Mac Adam: 3 Step  
Safety Class: II  
Working Temperature:-20°C to 55°C  
Life Time: 50,000hrs (L80/B10) at 35°C  
Warranty: 5 Years

### Parameter:


Wattage(W)	:	2W
Finish	:	Grey (G) / Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	80°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V
Type	:	Round (R) / Square(S)

### Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539058	02-2W	27-2700K	D- 24VDC	80-80°	G- Grey	1-ON/OFF
		30-3000K			C-Customized	2-DALI
		40-4000K				3-0/1-10V
		60-6000K				

Ex: Order Code: 5390580227D'80G1

### Photometric :



### Standard :

EN 60598-1  
EN 60598-2-2  
EN 60598-3-2  
EN 60598-3-3