


TARO



Description:

TARO is designed for reliable and efficient illumination in both exterior and interior environments. The housing is integrally die-cast aluminium, ensuring good heat dissipation. This fixture is ideal for architectural and functional lighting applications, offering dependable brightness and energy efficiency. Its robust design ensures resistance to outdoor conditions, making it suitable for a wide range of installations.

Product Specifications:

Housing : Die cast Aluminium
 Glass : Tempered Glass
 Diffuser : Clear Glass
 Gasket : Moulding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Surface mounted
 Adjustable: No

Technical Specifications:


Wattage: 30-50W
 Voltage: 220-240VAC
 Frequency: 50-60Hz
 Light Source: LumiLEDs
 Lumen: 125lm/W
 Mac Adam: 3 Step
 Safety Class: II
 Working Temperature:-20°C to 50°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Years

Parameter:

Wattage(W)	:	30W / 50W
Finish	:	Black (B)
Kelvin*	:	3000K / 4000K / 5000K / 5700K
Beam Angle	:	120°
CRI	:	80+
Control Mode	:	ON/OFF / DALI

Text Here...

Photometric :



Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540199	30-30W	30-3000K	A-220-240VAC	120-120°	B-Black	1-ON/OFF
	50 - 50W	40-4000K				2-DALI
		50 - 5000K				
		57-5700K				

Ex: Order Code: 5401993030A120B1

Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C