



TOYZ



Features:

Toyz Recessed Linear Light sleek, Modern, and clean finish.

The light made of high-quality aluminum body, acts as an effective heat sink, improving the lifespan of LEDs.

The aluminum has durability So that Corrosion-resistant and long-lasting, even in humid or demanding environments.

Excellent brightness with energy efficiency.

Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.

Wattage: 10-12W

High Lumen: 100lm/w

3 STEP Mac Adam

High efficiency, low flicker driver

Light Source: Bridgelux SMD2835

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at 25°C (L90/B20)

Fields of Application:

Retail

Galleries hotels

Living spaces

Conference rooms

Counters

Restaurants


Installation Method:

Recessed.

Wattage(W)	:	10	12			
Finish	:	White(W)	Black(B)			
Kelvin*	:	2700K	3000K	4000K	5000K	5700K
Beam Angle	:	40°	60°	80°		
CRI	:	80+	90+			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Cassambi




*Special Color & Finish on request

Product Code (96815112):

Wattage	Lumens(lm)	Dimension(LxWxH) mm	Cut out  (mm)
10	1000LM	151x43x61	115x37
12	1200LM	151x43x61	115x37

*Luminous flux value is calculated for 4000K CRI>80

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96815112 27K 40D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	40D - 40°	8->80	1 - ON/OFF	W-White
30K - 3000K	60D - 60°	9->90	2 - 0/1-10V	B-Black
40K - 4000K	80D - 80°		3 - DALI	
50K - 5000K			4 - Phase Dimming	
57K - 5700K			5 - Cassambi	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C