



TRAINING 48



Accessories:

Suspension Kit



Mounting Clips



Features:

TRAINING 48 Linear Extruded Aluminum Profile with highest standard 6063-T6 aluminum, deep anodizing (more than 12µm) that protects against corrosion and extends durability, Matt surface treatment.

Opal PC Diffuser / Micro Prismatic Lens / Prism Lens + Optics Diffusion sheet, all diffusers and lens are UV stabilized, no inclusions or scratches on the surface.

The inner radius is 45mm, and outer radius is 93mm.

Standard Length with Zagha Linear Modules 570 mm / 1200 mm/ 1480 mm/ 1920mm, tailored length can be manufactured as per design.

Homogenous, well-balanced light dispersing with no shadow.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.

Wattage /M: 40 - 115W

Efficacy: 145lm/w

3 STEP Mac Adam

High Efficiency, Low Flicker Driver

Lamp Type: Linear SMD VS Rigid

Module

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at ta 25°C

(L90/B10)

Fields of Application:

Retail

Education

Galleries hotels

Living spaces

Installation Method:

Surface / Suspended.

Wattage(W) :	40	55	70	90	115	
Finish :	White(W)	Black(B)	Silver(S)	Customized		
Kelvin* :	2700K	3000K	3500K	4000K	5000K	Tunable
Beam Angle :	120°					
CRI :	80+	90+	Tunable			
Driver :	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth	
Type :	A	B	C	D	E	

*Special Color and Finish on request

Product Code (9644878115):


Wattage	Lumens(lm)	Dimension(W XH) mm	Dimension (L1xL2xL3) mm
40	5800 LM	48x78	990x990x990
55	7925 LM	48x78	1120x1120x1120
70	10150 LM	48x78	1190x1190x1190
90	13050LM	48x78	1260x1260x1260
115	16675 LM	48x78	1540x1540x1540

*Luminous flux value is calculated for 4000K CRI>80

* Length and Wattage can be customized as per design

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 9644878115 27K 120D 8 1 W A

CCT	Beam Angle	CRI	Driver	Finish	Type
27K -	120D - 120°	8->80	1 - ON/OFF	W-White	A
2700K		9->90	2 - 0/1-10V	B-Black	B
30K -		T-	3 - DALI	S-Silver	C
3000K		>Tunable	4 - Phase	C-	D
35K -			Dimming	Customized	E
3500K			5 - Bluetooth		
40K -					
4000K					
50K -					
5000K					
TuK -					
Tunable					

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C