


TROFF



Accessories:

Suspension kit



Surface mounting frame



Features:

Simple and easy appearance, in line with contemporary aesthetic concept.

High Brightness LED comply with LM -80 standards.

No infrared rays, No ultraviolet radiation.

High visual comfort.

Frame: Aluminum

Casing: SPCC

Light diffuser: PC

LED lens: PMMA

Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.

Wattage: 30 - 35W

High Lumen: 140lm/w

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: SMD

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at ta 25°C

(L80/B10)

Fields of Application:

School

Offices

lobbies

Hallway

Hospital

Restaurant

Meeting Room

Installation Method:

Recessed/Surface/Suspended

Wattage(W)	:	30	32	35
Finish	:	White(W)		
Kelvin*	:	3000K	4000K	6500K
Beam Angle	:	120°		
CRI	:	80+	90+	
Driver	:	ON/OFF	0/1-10V	DALI Phase Dimming Bluetooth


*Special Color & Finish on request

Product Code (96659535):

Wattage	Lumens(lm)	Dimension(LxWx H) mm
30	4200LM	595X595X33
32	4480LM	595X595X33
35	4900LM	595X595X33

*Luminous øux value is calculated for 4000K CRI>80

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C

- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: <u>96659535</u> <u>30K</u> <u>120D</u> <u>8</u> <u>1</u> <u>W</u>				
CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	120D - 120°	8->80	1 - ON/OFF	W-White
40K - 4000K		9->90	2 - 0/1-10V	
65K - 6500K			3 - DALI	
			4 - Phase Dimming	
			5 - Bluetooth	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C