


UNEO



Features:

UNEO is Surface mounted light, have track rail for installed methods.
Track light also has with intrack adaptor and with gear box two options.
Good quality aluminum housing and special inner construction design to achieve excellent heat dissipation, with PC Lens medium and wide beam angle available. Anti-glare reflector color option is White, Black or Chrome.
Double Spring to fixing in the other side, can be connectable.
Very flexible, any length is available, meet different places high lumen requirements.
High efficiency and uniform lighting.
Uniform spot transition without residual light.
Homogenous, well-balanced light dispersing, no shadow.

Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.
Wattage: 12W
High Lumen: 95lm/w
3 STEP Mac Adam
High efficiency, low flicker driver
Lamp Type: SMD LED
Operating Temperature: -20°C to 45°C
Glow Wire Test 850° C
Warranty: 5 Years
Life Time: 50,000hrs at 25°C (L80/B10)

Fields of Application:

Retail
Galleries hotels
Living spaces
Conference rooms
Counters
Restaurants

Installation Method:

Surface Mounted.

Wattage(W)	:	12				
Finish	:	White(W)	Black(B)			
Kelvin*	:	2700K	3000K	4000K	5000K	5700K
Beam Angle	:	23°	50°			
CRI	:	80+	90+			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	


*Special Color & Finish on request

Product Code (96811812):

Wattage	Lumens(lm)	Dimension(LxWxH) mm
12	1425LM	118x44x75

*Luminous flux value is calculated for 4000K CRI>90

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C

- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 96811812 27K 23D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	23D - 23°	8->80	1 - ON/OFF	W-White
30K - 3000K	50D - 50°	9->90	2 - 0/1-10V	B-Black
40K - 4000K			3 - DALI	
50K - 5000K			4 - Phase Dimming	
57K - 5700K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C