

UNO



Features:

UNO is a Flood Light which is designed for durable and efficient outdoor lighting. Its die-cast aluminum housing with a polyester-sprayed surface provides shockproof and corrosion-resistant performance. The imported anti-aging rubber seal-ring ensures waterproofing and protection. A transparent tempered glass lamp enhances light transmission and durability. It also comes with adjustable bracket Base, Round Base and Stand Base. The honeycomb can make your lighting more dramatic or cinematic. Toughened glass surface, with high hardness, not easy to break. The UV-assisted and IR-free design protects illuminated objects. With gradual temperature increase, excellent heat dissipation, and waterproof sealing. Control Mode : DMX512

Product Specifications:

Housing : Die cast aluminum
 Front cover : Die cast aluminum
 Coating : Powder Coating
 Glass : Silver print
 Net Weight : 4.5KG
 Gasket : Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable : 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type : Surface Mounted
 Adjustable : Yes


Technical Specifications:

Wattage : 25 - 30W
 Voltage : DC24V
 Frequency : 50-60Hz
 Light Source : OSRAM / EPISTAR / CREE
 Lumen : 120lm/W
 Mac Adam : 3 Step
 Safety Class : III
 Working Temperature :-25°C to 50°C
 Life Time : 50,000hrs (L80/B10) at 35°C
 Warranty : 5 Years



Parameter:

Wattage(W)	:	25W / 30W
Finish	:	Black (B) / Customized (C)
Kelvin*	:	2700K / 3000K / 4000K / 6500K / RGB / RGBW
Beam Angle	:	8° / 15° / 30° / 45° / 60° / 15°x45° / 10°x 60°
CRI	:	80+ 90+
Driver	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut / DMX



Order Code :

Product Code	Type	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode	
545136	6-Spike	25 - 25W	27-2700K	D-24VDC	8 - 8°	B-Black	1-ON/OFF	
	7-Base	30 - 30W	30-3000K		15 - 15°	C-Customized	2-DALI	
	8-Hood				40-4000K	30 - 30°		3-0/1-10V
					65-6500K	45 - 45°		4-DMX
					92-RGB	60 - 60°		
					93-RGB DMX	15x45 - 15°x45°		
					82-RGBW	10x60- 10°x60°		
					83-RGBW DMX			

Ex: Order Code: 54513662527D'8B1

Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C