


VARLA



Description:

VARLA is a wall lamp. The design is simple and rich in texture. It is composed of die-casting aluminum.

The high-quality outdoor special powder coating process is adopted to make the lamp have strong weather resistance and anti-aging function.

High-transmission prismatic polycarbonate lens for uniform, glare-free illumination. 24V DC for DALI.

Standard product is ON/OFF, Sensor option available upon request.

It is ideal for building exteriors, entrances, pathways, and security lighting applications.

Product Specifications:

Housing : Die cast Aluminium
 Diffuser : PC
 UGR : <19
 Gasket: Moulding shaped silicone seal
 Power Cable: 0.5 mt. power cable included
 High efficiency, low flicker driver
 Installation Type: Surface mounted
 Adjustable: No

Technical Specifications:

Wattage: 20-30W
 Voltage: 220 - 240VAC
 Frequency: 50-60Hz
 Light Source: OSRAM
 Driver Brand: KGP/VS
 Lumen: 120lm/W
 Mac Adam: 3 Step
 Safety Class: III
 Working Temperature: -20°C to 50°C
 Life Time: 50,000hrs (L80/B10) at 25°C
 Warranty: 5 Years

Parameter:


Wattage(W)	: 20W / 30W
Finish	: Black (B) / Grey (G) / White (W)
Kelvin*	: 2700K/ 3000K/ 4000K / 6000K
Beam Angle	: 120°
CRI	: 80+ 90+
Control Mode	: ON/OFF / DALI

Order Code:

Product Code	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
540241	20-20W	27-2700K	A- 220-240VAC	D-Diffused	B-Black	1-ON/OFF
	30-30W	30-3000K			G-Grey	2-DALI
		40-4000K			W-White	
		60-6000K				

Ex: Order Code: 5402412027A'DB1

Photometric:



Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C