



VENUS



Sleeve (Included)



Description:

VENUS Wall light provide directional lighting to illuminate the steps evenly and prevent tripping hazards. The light is usually directed downward to focus on the walking path. This type of light fixtures are often designed to be weather-resistant, ensuring durability and functionality in various environmental conditions.

They utilize energy-efficient LED technology, offering longevity, low heat emission, and a variety of color options.

They serve both functional and aesthetic purposes, enhancing safety while contributing to the overall design of a space. For control integration, DALI compatibility is only available using a 24VDC power supply.

It is use for a specific application, it's essential to consider factors such as the level of illumination needed, the design aesthetic of the space, and any applicable safety regulations.

Product Specifications:

Front cover : Die cast Aluminium
 Housing : Die cast Aluminium
 Diffuser : Clear Glass
 Sleeve : Stainless Steel
 Gasket: Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Wall Recessed
 Adjustable: No

Technical Specifications:

Wattage: 12.5W
 Voltage: 24VDC / 220-240VAC
 Frequency: 50-60Hz
 Light Source: OSRAM/EPISTAR/CREE
 Driver Brand: KGP/VS
 Lumen: 40lm/W
 Mac Adam: 3 Step
 Safety Class: II
 Working Temperature: -20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Years

Parameter:

Wattage(W)	: 12.5W
Finish	: Grey (G) / Black (B) / White (W) / Customized (C)
Kelvin*	: 2700K / 3000K / 4000K / 6000K
Beam Angle	: Asymmetrical
CRI	: 80+ 90+
Control Mode	: ON/OFF / DALI


Text Here...

Order Code:

Product Code	Wattage	CCT	Voltage (DC)	Beam Angle	Finish	Control Mode
539161	12-12.5W	27-2700K	D-24VDC	80*30 -80*30°	G-Grey	1-ON/OFF
		30-3000K			B-Black	2-DALI
		40-4000K			W-White	
		60-6000K			C-Customized	

Ex: Order Code: 5391611227D'80*30G1

Photometric :



Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Product Code	Wattage	CCT	Voltage (AC)	Beam Angle	Finish	Control Mode
539161	12-12.5W	27-2700K	A-220-240VAC	80*30 -80*30°	G-Grey	1-ON/OFF
		30-3000K			B-Black	2-DALI
		40-4000K			W-White	
		60-6000K			C-Customized	

Ex: Order Code: 5391611227A'80*30G1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C