


VERO



Features:

VERO Series is Surface Mounted ceiling light with slim housing.

The body finish available with RAL 9003, and any other colors can be customized your requirements.

Heat sink Bottom is Flame-retardant ABS chassis, white spraying process, no yellowing with waterproof rubber ring.

Acrylic PMMA cover, light transmittance up to 90%, uniform light effect, no dark spots, slim design.

High thermal conductivity aluminum substrate with SMD LED Chips.

Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.

Wattage: 15-25W

High Lumen: 120lm/W

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: OSRAM 2835 SMD

Operating Temperature: -25°C to +50°C

Glow Wire Test 850°C

Warranty: 5 Years

Life Time: 50,000hrs at 25°C (L80/B10).

Fields of Application:

Retail

Kitchens

Washrooms

Corridors

Conference rooms

Restaurants

Lobbies

Installation Method:

Surface Mounted

Wattage(W)	:	15	20	25	25
Finish	:	White(W)			
Kelvin*	:	3000K	4000K	5000K	6000K
Beam Angle	:	120°			
CRI	:	80+	90+		
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming


*Special Color and Finish on request

Product Code (96817525):

Wattage	Lumens(lm)	Dimension(Ø x H) mm
15	1800LM	172x36
20	2400LM	172x36
25	3000LM	172x36

*Luminous flux value is calculated for 4000K CRI>80

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C

- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: <u>96817525</u> <u>30K</u> <u>120D</u> <u>8</u> <u>1</u> <u>W</u>				
CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	120D - 120°	8->80	1 - ON/OFF	W-White
40K - 4000K		9->90	2 - 0/1-10V	
50K - 5000K			3 - DALI	
60K - 6000K			4 - Phase Dimming	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C