



WARNA



Beam angle

Reflector Option -



Features:

WARNA is a recessed downlight, expertly crafted from Die cast aluminum and finished with a solvent-free powder coating to ensure long-lasting durability and resistance to wear.

It features a customized anti-glare reflector that supports multiple beam angles, achieving UGR <19 to ensure visual comfort in compliance with lighting standards.

Reflector color options are available in White and Black.

Homogenous, well-balance light dispersing, no shadow.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50/60Hz.

Wattage: 5 - 12W

Efficiency: 110lm/W

High efficiency, low flicker driver

3 STEP Mac Adam

Lamp Type: COB

Chip Brand : VS / Citizen / CREE

Operating Temperature: -20°C to 45°C

Glow Wire Test 960° C

Warranty: 5 Years

Lifetime 100,000hrs at a 25°C(L80/B10)

Fields of Application:

- Retail
- Education
- Galleries hotels
- Living spaces
- Museums
- Restaurants
- Painting Exhibitions
- Theaters

Installation Method:

Recessed

Wattage(W)	:	5	7	10	12
Finish	:	White(W)	Black(B)		
Kelvin*	:	2700K	3000K	3500K	4000K 5000K
Beam Angle	:	24°	36°	45°	60°
CRI	:	90+			
Driver	:	ON/OFF	DALI	Phase Dimming	0/1-10V


*Special Color and Finish on request

Product Code (98808214):

Wattage	Lumens(lm)	Dimension (ØxH) mm	Cut Out (mm)
5	550LM	82x60	75
7	770LM	82x60	75
10	1100LM	82x60	75
12	1320LM	82x60	75

*Luminous flux value is calculated for 4000K CRI>90,

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: ~~98808214~~ 27K 24D 9 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	24D - 24°	9->90	1 - ON/OFF	W-White
30K - 3000K	36D - 36°		2 - DALI	B-Black
35K - 3500K	45D - 45°		3 - Phase Dimming	
40K - 4000K	60D - 60°		4 - 0/1-10V	
50K - 5000K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C