WAVES WHITE



2835 SMD | 120° Beam Angle | LM80 | One Bin

3D Bend | Flame Resistant | UV Resistant | Salt Water Resistant | IK08 Protection

DESCRIPTION:

WAVES WHITE 3Dbend series constructed using Silicon extrusion process. Uniform, dot free light emission, good appearance consistency. Anti-yellowing, high temperature and corrosion resistance, weak acid and alkali resistance UV proof for true outdoor applications. Easy installation with clips and bendable track. Cutable for Flexible application.
Control mode : ON/OFF, DALI, Phase Cut, 0/1-10V.

TECHNICAL DETAILS:

Power : 5-15W/M
Voltage : DC24V
Efficiency : 70lm/W
CRI >90
3 step MacAdam
Length/Reel : 5M
Cutting length : 8.33mm
Led Qty : 120LEDs/M
Working Temperature : -25~60°C
Storage Temperature : -25~70°C
Voltage Range : 23~25V dc
Reverse Voltage : 25V dc
Warranty : 5 years

LUMENS PER METER:


CCT	5W	10W	15W
2700K	332lm	665lm	998lm
3000K	350lm	700lm	1050lm
4000K	367lm	735lm	1103lm
5000K	369lm	738lm	1108lm
5700K	371lm	742lm	1113lm
6500K	378lm	756lm	1134lm

INSTALLATION :


Horizontal and Vertical Bend


Product Code : 6301212

DIMENSION:




LIGHT DISTRIBUTION:






BENDING:




End cap

Wire at end



Wire at side



Wire at bottom



Standards
EN 60598-1
EN 60598-2-2
EN 60598-3-2


Order Code Ex : 6301212

Product Code	Power	CCT
6301212	05-5W	27-2700K
	10-10W	30-3000K
	15-15W	40-4000K
		50-5000K
		57-5700K
		65-6500K

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Pluxb Lighting d.o.o
Miklavška cesta 75, SI - 2311 Hoce, SLOVENIA
www.pluxb.com

ACCESSORIES




Aluminium Profile
Order Code : 6301212-01
Dimension : L1000xW14xH14.6mm
Material : Aluminium
Color : Silver



End Cap 2PIN
Order Code : 6301212-06
Color : White
Cable entry : Front/Side/Bottom
Picture : Front



Curved Profile
Order Code : 6301212-02
Dimension : L1000xW13.6xH14.1mm
Material : Stainless Steel
Color : Silver



Closed End Cap
Order Code : 6301212-07
Material : Silicone
Color : White



Mounting Clips
Order Code : 6301212-03
Dimension : L30xW14xH14.6mm
Material : Stainless steel
Color : Silver
Each meter led strips needs
2 clips + 2 screws



IP67 T Type Connector
Order Code : 6301212-08
Wire Gauge : 0.326mm^2/22AWG
Protection : IP67 (Mated)



IP67 Connector 2PIN
Order Code : 6301212-04
Wire gauge : 0.326mm^2/22AWG
Protection : IP67 (Mated)
Connector type : Male




Scissor
Order Code : 6301212-09



IP67 Connector 2PIN
Order Code : 6301212-05
Wire gauge : 0.326mm^2/22AWG
Protection : IP67 (Mated)
Connector type : Female

ADDITIONAL INFO




- Please light it up for a quick check before installation.

- Bending diameter of WAVES WHITE 3D 1212 is 200mm, Do not bend too sharp or twist. If bend it wrongly, PCB inside will be damaged and the lighting fixture will not turn on.

- During installation, please make sure there are at least two workers to cooperate together and strictly follow the instruction manuals.

- Warranty : All LED light are warranted to be free from defects in product itself for 5 years from the date of purchase. This warranty does not cover failures due to abuse, misuse, improper handling, act of nature, negligence, normal wear, accidental damage, repairs made by the purchaser or incorrect voltage conditions.




Note:
-5W/M Max. 10mtr run length to single side feed.
-10W/M Max. 10mtr run length to single side feed.
-15W/M Max. 7mtr run length to double side feed.


-The given data are typical values due to the tolerances of the production process and the electrical components, values for light output and electrical power can vary up to 5%.

WIRING DIAGRAM


ON/OFF



1. DALI




2. WITH PUSH DIM




WIRING DIAGRAM

0/1-10V



PHASE CUT





GENERAL MOUNTING

LED neon flex can be fastened to surfaces using appropriate accessories available from distributor. Please refer to data sheets or contact technical support for a copy. The use of glues and resins as fixing agents should be avoided. Use of glues and resins may invalidate the warranty of the product unless it's use is agreed in writing by distributor as part of a detailed project specification.


The images indicate one type of fixing available in the accessories range. The different fixings serve obvious purposes, however when in doubt technical support should be contacted.


Quantities of accessories and fixings are dependent on the type and its effect on the variant it's being used with. Care should be taken to ensure drooping is avoided, and to ensure that is fastened adequately to avoid stresses on itself.






Press the flex light into mounted aluminum channel in one direction.







Do not bend against light terminals; otherwise it will lead to failure of connector waterproof.


Incorrect installation like below picture could lead to light failure.









Ensure the feeding cable not bear force, keep the head10mm in natural loose.






Mount the cable junction in hermetic enclosure
like waterproof junction box in outdoor application.




INSTALLATION


Attention




1. Correct bending way.


Installation







1. During LED strip installation, ensure to uncoil the strip loop by loop and maintain perpendicular alignment with the mounting profile. Avoid twisting or knoting of the strip at all times.






2. Align the LED strip with the opening of the profile, gently lift and press the strip into the profile, and strictly avoid excessive bending or lifting of the strip.






3. Align the LED strip with the opening of the profile, gently lift and press the strip into the profile, and strictly avoid excessive bending or lifting of the strip.




The safe tensile force for the LED strip shall be ≤4ON
Excessive force may damage the internal circuitry.




The safe twisting angle for the LED strip shall not exceed 180°.


Warning sign




Cuttable Marking Area
(on the bottom or side of the product).




Neat and smooth cut.




Mount the roll on a rod over the box and rotate to use.




Top Bend.




Side Bend.




Free Bend.




Do not leave uneven cuts.




Do not twist during use.




Repeated bending may damage electronic circuits.



Do not puncture or scratch with sharp objects.



Do not bend at sharp angles.



Do not jerkor yankwhen using the product.

1. The cutting marks are located on the PCB. Refer to the product cutting line window or laser markings von the surface to identify the trimming position.

2. During transportation and application, please observe the above warning labels. Proper handling ensures optimal performance and user satisfaction.

Pluxb Lighting d.o.o
Miklavška cesta 75, SI - 2311 Hoce, SLOVENIA

www.pluxb.com