


WILL



Description:

WILL is a Recessed Wall Mounted provide directional lighting to illuminate the steps evenly and prevent tripping hazards.

The light is usually directed downward to focus on the walking path.

This type of light fixtures are often designed to be weather-resistant, ensuring durability and functionality in various environmental conditions. With THD less than 10% and a power factor greater than 0.9, it ensures high electrical efficiency and superior performance.

They utilize energy-efficient LED technology and Anti Glare, offering longevity, low heat emission, and a variety of color options.

They serve both functional and aesthetic purposes, enhancing safety while contributing to the overall design of a space.

It is use for a specific application, it's essential to consider factors such as the level of illumination needed, the design aesthetic of the space, and any applicable safety regulations.


Product Specifications:

Front cover : Die cast Aluminium
Housing : Die cast Aluminium
Diffuser : Opal PC
Gasket: Molding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Wall Recessed
Adjustable: No

Technical Specifications:

Wattage: 1.4W
Voltage: 24VDC
Frequency: 50-60Hz
Light Source: OSRAM/EPISTAR/CREE
Lumen: 80lm/W
Mac Adam: 3 Step
Safety Class: III
Cut out : L74*W58*H46mm
Working Temperature:-20°C to 50°C
Life Time: 50,000hrs (L80/B10) at 25°C
Warranty: 5 Years

Photometric:



Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Parameter:

Wattage(W)	:	1.4W
Finish	:	Grey (G) / Black (B) / White (W) / Customized (C)
Kelvin*	:	2700K / 3000K / 4000K / 6000K
Beam Angle	:	Assymetric
CRI	:	80+
Control Mode	:	ON/OFF / DALI

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539077	01 - 1.4W	27-2700K	D - 24VDC	AS - Assymetric	G-Grey	1-ON/OFF
		30-3000K			B-Black	2-DALI
		40-4000K			W-White	
		60-6000K			C-Customized	

Ex: Order Code: 5390770127D'ASG1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C