


## WILL



### Description:

WILL is a Recessed Wall Mounted provide directional lighting to illuminate the steps evenly and prevent tripping hazards. The light is usually directed downward to focus on the walking path.

This type of light fixtures are often designed to be weather-resistant, ensuring durability and functionality in various environmental conditions. With THD less than 10% and a power factor greater than 0.9, it ensures high electrical efficiency and superior performance.

They utilize energy-efficient LED technology and Anti Glare, offering longevity, low heat emission, and a variety of color options.

They serve both functional and aesthetic purposes, enhancing safety while contributing to the overall design of a space

It is use for a specific application, it's essential to consider factors such as the level of illumination needed, the design aesthetic of the space, and any applicable safety regulations.


### Product Specifications:

Front cover : Die cast Aluminium  
Housing : Die cast Aluminium  
Diffuser : Opal PC  
Gasket: Molding shaped silicone seal  
Lens/Reflector : Optical lens (efficiency>90%)  
Power Cable: 0.5 mt. power cable included  
Driver : High efficiency, low flicker driver  
Installation Type: Wall Recessed  
Adjustable: No

### Technical Specifications:

Wattage: 11W  
Voltage: 24VDC  
Frequency: 50-60Hz  
Light Source: OSRAM/EPISTAR/CREE  
Lumen: 80lm/W  
Mac Adam: 3 Step  
Safety Class: III  
Cut out : L333\*W58\*H46mm  
Working Temperature:-20°C to 50°C  
Life Time: 50,000hrs (L80/B10) at 25°C  
Warranty: 5 Years

### Photometric:



### Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

### Parameter:

Wattage(W)	:	11W
Finish	:	Grey (G) / Black (B) / White (W) / Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	Assymetric
CRI	:	80+
Control Mode	:	ON/OFF / DALI

### Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539334	11 - 11W	27-2700K	D - 24VDC	AS - Assymetric	G-Grey	1-ON/OFF
		30-3000K			B-Black	2-DALI
		40-4000K			W-White	
		60-6000K			C-Customized	

**Ex: Order Code:** 5393341127D'ASG1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C