
pluxb

IP65 IK08

WILLOW





Description:

WILLOW is a outdoor wall downlight features a sleek cylindrical design with a compact wall-mounted profile, delivering focused downward illumination for both indoor and outdoor applications. Its aluminium construction provides durability while maintaining a clean and contemporary architectural appearance.

Available with multiple beam angles and LED colour temperatures, it offers flexible lighting options for different environments and design requirements. With an IP65 rating, the fixture is well suited for exterior walls, entrances, pathways, terraces, façades, and other architectural spaces requiring reliable and refined accent lighting.

Product Specifications:

Housing : Die cast Aluminium
Diffuser : Tempered Glass
Coating : Powder Coating
Light Source: OSRAM / CREE
Gasket: Moulding shaped silicone seal
Power Cable: 0.5 mt. power cable
Driver : High efficiency, low flicker driver
Installation Type: Wall mounted
Adjustable: No

Technical Specifications:

Wattage: 7W
Voltage: 220-240VAC, 50-60Hz
Lumen: 55lm/W
Mac Adam: 3 Step
Safety Class: III
Dimension : D60*H125mm
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	7W
Finish	:	Black (B) / White (W) / Bronze (BR) / Copper (CP)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	15° / 24° / 36°
CRI	:	80+ 90+
Control Mode	:	ON/OFF DALI

*Lumen values are calculated at 36° beam angle, 4000K color temperature and CRI 80.

Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3


Order Code:


Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540060	07 - 7W	27-2700K	A-220-240VAC	15-15°	B-Black	1-ON/OFF
		30-3000K		24-24°	W - White	2-DALI
		40-4000K		36-36°	BR - Bronze	
		60-6000K			CP - Copper	


Ex: Order Code: 5400600727A'15B1

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C







Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C