



WOLF



Features:

WOLF Magnetic Linear Luminaire features a premium die-cast aluminum housing with a high-transmittance PC opal diffuser, providing excellent light transmission and enhanced durability. Designed to deliver soft, uniform, and glare-controlled illumination, it ensures comfortable visual performance with homogeneous light distribution and no visible shadow. Compatible with 48V low-voltage magnetic track systems, the luminaire provides a safe, efficient.

The integrated magnetic mounting system allows for quick, tool-free installation and flexible repositioning along the track, offering maximum convenience and adaptability for various lighting layouts.

Combining refined aesthetics, advanced optical performance, and flexible installation, the product Magnetic Linear Luminaire creates a clean and elegant lighting environment with balanced illumination and superior visual comfort.

Technical Specifications:

Input Voltage: 48V AC, 50 Hz.
 Wattage: 25-27W
 High Lumen: 103lm/W
 3 STEP Mac Adam
 High efficiency, low Flicker driver
 Lamp Type: SMD
 Chip Brand: CREE / Bridgelux
 Driver Brand: VS / Philips
 Operating Temperature: -20°C to 45°C
 Glow Wire Test 850° C
 Warranty: 5 Years
 Life Time: 50,000hrs at 25°C (L85/B10).

Fields of Application:

Commercial places
 Galleries hotels
 Car displays
 Museums
 Restaurants
 Clothing shops
 Furniture Shops
 Architectural Lighting

Installation Method:

On an electrified track or special base.

Wattage(W)	:	25	27				
Finish	:	Matte White(W)	Matte Black(B)				
Kelvin*	:	2700K	3000K	3500K	4000K	5700K	6500K
Beam Angle	:	90°					
CRI	:	80+	90+				
Driver	:	ON/OFF	0/1-10V	DALI	Casambi		


*Special Color and Finish on request

Product Code (66565227):

Wattage	Lumens(lm)	Dimension(L x W) mm
25	2575LM	652x22
27	2781LM	652x22

*Luminous flux value is calculated for 3000K and CRI>90, 3 STEP Mac Adam.

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 66565227 27K 90D 8 1 M

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	90D - 90°	8->80	1 - ON/OFF	M-Matte White
30K - 3000K		9->90	2 - 0/1-10V	M-Matte Black
35K - 3500K			3 - DALI	
40K - 4000K			4 - Casambi	
57K - 5700K				
65K - 6500K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C