


WOUP



Features:

The Woup Recessed spotlight has a modern, minimalist, sleek, Reliable Performance design that is compatible with any contemporary interior.

The aluminum body is both durable and produces better heat dissipation while still providing optimum value - with a detachable bezel.

High quality, impact resistant materials make up the lens so that your workloads and / or environmental conditions will not affect the quality of the light being outputted.

The product comes with decorative baffle in matt white/black/silver/gold finishing

Designed to meet a UGR > 19 rating, provides comfortable, glare-proof, bone-ideal illumination.

Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.

Wattage: 10W

Efficacy: 90lm/W

High efficiency, low flicker driver

2 / 3 STEP Mac Adam

Lamp Type: COB

Light source: Citizen / CREE

Operating Temperature: -20°C to 45°C

Glow Wire Test 850°C

Warranty: 5 Years

Life Time: 50,000hrs at 25°C

(L80/B10).

Fields of Application:

Retail

Galleries hotels

Living spaces

Conference rooms

Counters

Restaurants

Installation Method:

Recessed.

Wattage(W)	:	10				
Finish	:	White (W)	Black (B)	Silver (S)	Gold (G)	
Kelvin*	:	2700K	3000K	4000K	5700K	6500K
Beam Angle	:	24°	36°	60°		
CRI	:	90+				
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Casambi




*Special Color and Finish on request

Product Code (96707510):

Wattage	Lumens(lm)	Dimension(Ø x H) mm	Cut Out() mm
10	900LM	75x53	65

*Luminous flux value is calculated for 4000K CRI>90, 3 STEP Mac Adam

Photometric:



- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 96707510 27K 24D 9 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	24D - 24°	9->90	1 - ON/OFF	W-White
30K - 3000K	36D - 36°		2 - 0/1-10V	B-Black
40K - 4000K	60D - 60°		3 - DALI	S-Silver
57K - 5700K			4 - Phase Dimming	G-Gold
65K - 6500K			5 - Casambi	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C