



YARD



Features:

Yard is a versatile recessed panel light that can easily be mounted in a ceiling recess. The luminaire is available in a variety of power and color temperatures, and it includes features such as motion detection, timer, sleep, and twilight function. These high-quality fixtures provide even and glare-free illumination, creating a comfortable and productive environment for any setting.

Technical Specifications:

Input Voltage : 220- 240 V AC, 50 Hz.
Wattage : 32-40W
High Efficacy : 100lm/w
3 STEP Mac Adam
High efficiency, low Flicker driver
Lamp Type : LED
Operating Temperature: -20°C to 45°C
Glow Wire Test 850° C
Warranty : 5 Years
Life Time : 50,000hrs at 25°C (L80/B10)

Fields of Application:

Retail
Education
Galleries hotels
Living spaces
Conference rooms
Counters
Restaurants

Installation Method:

Recessed/Surface/Suspended

Wattage(W)	:	32	35	40
Finish	:	White(W)		
Kelvin*	:	3000K	4000K	6500K
Beam Angle	:	120°		
CRI	:	80+	90+	
Driver	:	ON/OFF	0/1-10V	DALI Phase Dimming Bluetooth


*Special Color & Finish on request

Product Code (96659740):

Wattage	Lumens(lm)	Dimension(LxWx H) mm
32	3200LM	597x597X35
35	3500LM	597x597X35
40	4000LM	597x597X35

*Luminous flux value is calculated for 4000K CRI>80

Photometric:



- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 96659740 30K 120D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	120D - 120°	8->80	1 - ON/OFF	W-White
40K - 4000K		9->90	2 - 0/1-10V	
65K - 6500K			3 - DALI	
			4 - Phase Dimming	
			5 - Bluetooth	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C