

ZIN




Description:

ZIN is wall down light fixture designed to illuminate downward directions. It is typically installed on vertical surfaces such as walls to create a balanced and aesthetically pleasing lighting effect.

These lights often contribute to ambient lighting and can enhance the visual appeal of indoor or outdoor spaces.

They come in various designs, wattages, and light sources, providing flexibility for different lighting preferences and applications.

It has very wide application like For enhance architectural features and provide ambient lighting in residential and commercial spaces, adding both style and functionality.



Product Specifications:

Housing : Die cast Aluminium grey
Diffuser : Tempered Glass
Reflector : Anodized Aluminium
Gasket: Moulding shaped silicone seal
Power Cable: 0.5 mt. power cable
Driver : High efficiency, low flicker driver
Installation Type: Wall mounted
Adjustable: No

Technical Specifications:

Wattage: 3W
Voltage: 85-265VAC, 50-60Hz
Light Source: OSRAM/EPISTAR/CREE
Lumen: 100lm/W
Mac Adam: 3 Step
Safety Class: II
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:


Wattage(W)	:	3W
Finish	:	Grey (G) /Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	120°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540081	03-3W	27-2700K	A-220-240VAC	120-120°	G-Grey	1-ON/OFF
		30-3000K			C-Customized	2-DALI
		40-4000K				3-0/1-10V
		60-6000K				

Ex: Order Code: 5400810327A'120G1

Photometric:



Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C