


## ZOBRA



### Features:

ZOBRA Is Decorative Magnetic track light installed on Low Voltage and wattage Magnetic Track.

Available in different styles and finishes to match various interior decors.

Body Material made of aluminum with LED technology for energy savings and longevity.

This is ideal for highlighting specific objects or areas.

Low-voltage DC40V input scheme is adopted.

The magnetic track allows you to easily move and adjust the position of the light fixture along the track.

### Technical Specifications:

Input Voltage: 40V DC, 50 Hz.

Wattage: 18-36W

High Lumen: 100lm/w

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: SMD Module

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at ta 25°C

(L80/B10)

### Fields of Application:

Retail

Education

Galleries hotels

Living spaces

### Installation Method:

On an electrified Magnetic track 40V DC

Wattage(W)	:	18	36		
Finish	:	White(W)	Black(B)	Gray(G)	
Kelvin*	:	2700K	3000K	4000K	5000K
Beam Angle	:	120°			
CRI	:	80+	90+		
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming Bluetooth


\*Special Color and Finish on request

### Product Code (76511436):

Wattage	Lumens(lm)	Dimension (LxWxH) mm
18	1800LM	114x22x1070
36	3600LM	114x22x2070

\*Luminous lux value is calculated for 4000K CRI>90

### Photometric:



- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 76511436 27K 120D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	120D - 120°	8->80	1 - ON/OFF	W-White
30K - 3000K		9->90	2 - 0/1-10V	B-Black
40K - 4000K			3 - DALI	G-Gray
50K - 5000K			4 - Phase Dimming	
			5 - Bluetooth	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C